



Image shown may not reflect actual package.

PRIME

728 ekW 910 kVA

50 Hz 1500 rpm 400 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low fuel consumption

DESIGN CRITERIA

- The generator set accepts 100% rated load in one step and meets ISO 8528-5 transient response.

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Caterpillar® dealers provide extensive post sale support including maintenance and repair agreements
- Caterpillar dealers have over 1,600 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT C32 ATAAC DIESEL ENGINE

- Utilizes ACERT™ Technology
- Reliable, rugged, durable design
- Four-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

CAT GENERATOR

- Designed to match the performance and output characteristics of Caterpillar diesel engines
- Single point access to accessory connections
- UL 1446 recognized Class H insulation

CAT EMCP 3 SERIES CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

PRIME 728 kW 910 kVA

50 Hz 1500 rpm 400 Volts



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Single element canister type air cleaner • Service indicator 	<ul style="list-style-type: none"> • Dual element air cleaners • Air inlet adapters
Cooling	<ul style="list-style-type: none"> • Radiator with guard (43°C) • Low profile (frontal area) • Low airflow • Coolant drain line with valve • Fan and belt guards • Caterpillar Extended Life Coolant • Coolant level sensors • Radiator duct flange 	<ul style="list-style-type: none"> • Radiator with 27°C ambient capability • Jacket water heater
Exhaust	<ul style="list-style-type: none"> • Dry exhaust manifold • Flanged faced outlets 	<ul style="list-style-type: none"> • Stainless steel exhaust flex fittings • Elbows, flanges, expanders & Y adapters
Fuel	<ul style="list-style-type: none"> • Primary fuel filter with water separator • Secondary fuel filter • Fuel priming pump • Flexible fuel lines • Fuel cooler 	
Generators	<ul style="list-style-type: none"> • Class H insulation • Class F temperature (105°C prime/130°C standby) • Winding temperature detectors (select models) • Anti-condensation space heaters 	<ul style="list-style-type: none"> • Oversize & premium generators
Power Termination	<ul style="list-style-type: none"> • Bus bar (NEMA and IEC mechanical lug holes) -right side standard • Bottom cable entry 	<ul style="list-style-type: none"> • Circuit breakers, UL listed, 3 pole with shunt trip, 100% rated, choice of trip units, manual or electrically operated (low voltage only) • Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip (low voltage only), choice of trip units, manual or electrically operated • Shroud cover for bottom cable entry • Power terminations can be located on the left and/or rear as an option. Also, multiple circuit breakers can be ordered (up to 2) • Top cable entry
Governor	<ul style="list-style-type: none"> • ADEM™ A4 	<ul style="list-style-type: none"> • Load Share Module
Control Panels	<ul style="list-style-type: none"> • EMCP 3.1 • User Interface panel (UIP) - rear mount • Emergency Stop Push button 	<ul style="list-style-type: none"> • EMCP 3.2 and EMCP 3.3 • Right or left mount UIP • Local & remote annunciator modules • Discrete I/O Module • Generator temperature monitoring & protection • Load share module
Lube	<ul style="list-style-type: none"> • Lubricating oil and filter • Oil drain line with valves • Fumes disposal • Gear type lube oil pump 	<ul style="list-style-type: none"> • Deep sump oil pan
Mounting	<ul style="list-style-type: none"> • Formed steel welded base • Anti-vibration mounts (shipped loose) 	
Starting/Charging	<ul style="list-style-type: none"> • 24 volt starting motor(s) • Batteries with rack and cables • Battery disconnect 	<ul style="list-style-type: none"> • Battery chargers (10 Amp) • 45 amp charging alternator • Oversize batteries • Ether starting aid
General	<ul style="list-style-type: none"> • Right-hand service • Paint - Caterpillar Yellow (except rails and radiators that are gloss black) • SAE standard rotation • Flywheel and Flywheel housing - SAE No. 0 	<ul style="list-style-type: none"> • UL 2200 • CSA certification • EU Declaration of Incorporation • EEC Declaration of Conformity

SPECIFICATIONS

CAT GENERATOR

SR4B Generator

Frame size.....	692
Excitation.....	Permanent Magnet
Pitch.....	0.7143
Number of poles.....	4
Number of bearings.....	2
Number of Leads.....	12
Insulation.....	UL 1446 Recognized Class H with tropicalization and antiabrasion
IP rating.....	Drip Proof IP22
Alignment.....	Close Coupled
Overspeed capability - % of rated.....	180
Wave form.....	003.00
Voltage regulator.....	3 Phase sensing with selectable volts/Hz
Voltage regulation.....	Less than +/- 1/2% (steady state)
	Less than +/- 1% (no load to full load)
Telephone Influence Factor.....	Less than 50
Harmonic distortion.....	Less than 5%

CAT DIESEL ENGINE

C32 TA, V-12, 4-stroke watercooled diesel

Bore - mm.....	145.00 mm (5.71 in)
Stroke - mm.....	162.00 mm (6.38 in)
Displacement - L.....	32.10 L (1958.86 in ³)
Compression ratio.....	15:1
Aspiration.....	TA
Fuel system.....	MEUI
Governor type.....	ADEM™ A4

CAT EMCP 3 SERIES CONTROLS

- 12-24 Volt (nominal) DC Control
- Run/Auto/Stop control
- Display Size 24 x 95 mm
- Display Size 33 x 132 (pixels)
- Display available in any of 26 languages with text translation capability
- Temperature operating range -40C to 70C (display to -20C)
- Designed for mounting on generator set package (vibration tested to 4.3G sinusoidal and 15G shock)
- 3-phase, true RMS metering
- Generator metering accuracy (+/- 2%)
- Metering - L-L volts, L-N volts, phase Amps, Hz
- Digital indications for RPM, operating hours, oil pressure, coolant temperature and system DC voltage
- LED indicators for warning/shutdown alarms (low oil pressure, high coolant temperature, low coolant, over-speed, etc)
- Reset all events function
- Voltage adjust when CDVR is on J1939 data-link
- Integrates with Adem engine governor for engine monitoring, alarms and control
- Integrates with Caterpillar Digital Regulator (CDVR) for alarms and control
- Compatible with Caterpillar ET service tool for enhanced serviceability including data capturing from event log, data logging, set point programming and troubleshooting
- Field re-flashable software ensures the customers get the latest updated software
- Programmable switch inputs
- Programmable relay outputs (2A continuous DC)

PRIME 728 kW 910 kVA

50 Hz 1500 rpm 400 Volts



TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM9047	
Low Fuel Consumption		
Generator Set Package Performance Genset Power rating @ 0.8 pf Genset Power rating with fan	910 kVA 728 kW	
Coolant to aftercooler Coolant to aftercooler temp max	49 ° C	120 ° F
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	195.3 L/hr 150.7 L/hr 107.8 L/hr	51.6 Gal/hr 39.8 Gal/hr 28.5 Gal/hr
Cooling System¹ Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 1021 m ³ /min 190.0 L 55.0 L 135.0 L	0.48 in. water 36056 cfm 50.2 gal 14.5 gal 35.7 gal
Inlet Air Combustion air inlet flow rate	51.2 m ³ /min	1808.1 cfm
Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	552.0 ° C 150.0 m ³ /min 203 mm 10.0 kPa	1025.6 ° F 5297.2 cfm 8 in 40.2 in. water
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	306 kW 699 kW 101 kW 176 kW 41.6 kW	17402 Btu/min 39752 Btu/min 5744 Btu/min 10009 Btu/min 2365.8 Btu/min
Alternator² Motor starting capability @ 30% voltage dip Frame Temperature Rise	1694 skVA 692 105 ° C	189 ° F
Lube System Sump refill with filter	68.0 L	18.0 gal
Emissions (Nominal)³ NOx mg/nm ³ CO mg/nm ³ HC mg/nm ³ PM mg/nm ³	2940.5 mg/nm ³ 350.9 mg/nm ³ 5.1 mg/nm ³ 9.9 mg/nm ³	

¹ For ambient and altitude capabilities consult your Caterpillar dealer. Air flow restriction (system) is added to existing restriction from factory.

² UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40°C ambient per NEMA MG1-32.

³ Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

PRIME 728 ekW 910 kVA

50 Hz 1500 rpm 400 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034, ISO 3046, ISO 8528, NEMA MG 1-33, UL508A, 98/37/EC

Prime - Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year. Prime power in accordance with ISO 3046. Prime ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the alarm temperature.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO 3046 standard conditions.

Fuel rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Caterpillar representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Caterpillar dealer.

PRIME 728 ekW 910 kVA

50 Hz 1500 rpm 400 Volts



DIMENSIONS

Package Dimensions		
Length	4666.9 mm	183.74 in
Width	2044.4 mm	80.49 in
Height	2202.2 mm	86.7 in
Weight	8046 kg	17,738 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2763027).

Performance No.: DM9047

Feature Code: C32DE01

Gen. Arr. Number: 2628092

Source: U.S. Sourced

www.CAT-ElectricPower.com

© 2008 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, SAFETY.CAT.COM their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.